



3D VIS FRONT



CHAMELEON FRONT



Coca-Cola 3D VIS & Chameleon Stack
Vending Line

ISO9001:2015, ISO1400:2015, ISO/IEC 17025:2005, and OSHAS 18001 certified.



Model		621	721	821
Total Can Capacity		544	680	800
Total PET Bottle Capacity		240	300	360
Selection Spaces/Columns		6/8	8/10	8/10
Dimensions H x W x D	3D VIS Front	72" x 32.5" x 35"	72" x 39.5" x 35"	79" x 39.5" x 35"
	Chameleon Front	72" x 32.5" x 35"	72" x 39.5" x 35"	79" x 39.5" x 35"
Shipping Weight*		570 lbs	660 lbs	725 lbs
Operation Voltage		115v 60Hz		
Amp Rating		8		
Energy Consumption		2.66 kWh/day	2.91 kWh/day	2.67 kWh/day
Lighting		LED		
Refrigerant		R-290		
Lock Type		T-Handle		
Capacity per Column	12 oz Can	68		80
	20 oz PET Bottle**	30		36

* Dimensions and shipping weight will vary slightly.

** Product capacities will vary based on the shape and size of the bottle.

Refrigerant	R-134a	R-290
Ozone Destructive Potential	0	0
Global Warming Potential	1,430	3
Operating High Side Pressure	150 PSig	200 PSig

At SandenVendo America, we take our commitment to the environment very seriously. That's why we're proud to offer our full range of vending machines charged with R290 HC. R290 is a safe and abundant natural refrigerant with a zero Ozone Depleting Potential and a Global Warming Potential (GWP) of 3, compared to HFC - R134a's GWP of 1,430, proving to be the sustainable choice of the future.

***Mounting brackets secured to the door frame with carriage bolts provide optimum security and ease of installation. Permanent studs protrude through pre-drilled holes on the door frame to reduce vandalism and ensure the door is tamper resistant.

The classic column stack machine features flexible product loading, interchangeable control boards, self-priming vend mechanisms, energy efficiency, reliable vending, and easy servicing.

Full function MDB controller with DEX/UCS, recycler and wireless telemetry compatibility standard on all models. The time tested product delivery system ensures reliable vending. The epoxy coated vend chute provides smooth product delivery and rugged top retainer ensures consistent product alignment every time the door is closed.

Vend mechanisms are self-priming. Slide out loading rack allows for greater access to columns. For maximum flexibility, products can be loaded caps to back, butt-to-butt, or in combination. 24 volt, DC motors are installed with only two screws for easy servicing. No micro-switches, timing cams, shims, spacers, gauge bars, or gauge bar clips.



SandenVendo America, Inc
www.vendoco.com
+1 800 344 7216