



3D VIS & Chameleon Stack Vendor

FEATURES & BENEFITS


The V21 offers fast set-up. Converting columns from bottles to cans has never been easier!

- No shims, spacers, guage bars, guage bar clips, or cams to adjust.
- Vend-mechanisms are self-priming for additional time-savings at product set-up.
- Simply move the back spacer, adjust the product slide and select the appropriate depth setting to set-up a column for a different vend product.
- Slide out loading rack allows for greater access to the columns during product loading.



- Rugged top retainer ensures consistent product alignment every time the door is closed.
- The V21's epoxy coated vend chute provides smooth product delivery.
- Mounting brackets secured to the door frame with carriage bolts provide optimum security and

ease of installation. Permanent studs protrude through pre-drilled holes on the door frame to reduce vandalism and ensure the door is tamper resistant.





At SandenVendo America, we take our commitment to the environment very seriously. That's why we're proud to offer our full range of vending machines charged with R290 HC. All models are cUL listed and meet or exceed DOE and Energy Star requirements. R290 is a safe and abundant natural refrigerant with a zero Ozone Depleting Potential and a Global Warming Potential (GWP) of 3, compared to HFC - R134a's GWP of 1,430, so it's clear that R290 is the sustainable choice of the future.



R-290 (HC) vs. R-134a Over 100 Years

Refrigerant	R-134a	R-290
Ozone Destructive Potential	0	0
Global Warming Potential	1,430	3
Operating High Side Pressure	150 PSIg	200 PSIg

(instead of 9 inches).

All models in the V21 Equipment Line meet the current Americans with Disabilities Act 2010 Standards for

Accessible Design. The reach range requirements have been changed to provide that the side reach range must now be no higher than 48 inches (instead of

54 inches) and no lower than 15 inches

Energy STAR

All models in the V21 Equipment Line are ENERGY STAR qualified and meet or exceed the Department of Energy 2012 Efficiency Standards. Refrigerated beverage vending machines that have earned the ENERGY STAR are up to 50% more energy-efficient than standard machine models. ENERGY STAR qualified machines come with a low power mode option that allows the machine to be placed in low-energy lighting and/or low-energy refrigeration states during periods of inactivity.



COMPL

Side reach no

OS FOR ACCES

SandenVendo America, Inc.

10710 Sanden Drive, Dallas, TX 75238 P: 214-765-9066 F: 214-340-8029 P: 1-800-344-7216 F: 1-800-541-5684

www.vendoco.com



Copyright © 2018 SVA





3D VIS & Chameleon Stack Vendor

FEATURES & SPECIFICATIONS

V21 Model Number	621	721	821
Total Can Capacity	544	680	800
Total PET Bottle Capacity	240	300	360
# of Selections / Columns	6/8	8 / 10	8/10
Dimensions* - H x W x D			
3D VIS Front	72" x 32.5" x 35"	72" x 39.5" x 35"	79" x 39.5" x 35"
Chameleon Front	72" x 32.5" x 35"	72" x 39.5" x 35"	79" x 39.5" x 35"
Flat Front	72" x 32.5" x 31"	N/A	N/A
Shipping Weight*	570 lbs.	660 lbs.	725 lbs.
Operation Voltage	115v 60Hz	115v 60Hz	115v 60Hz
Amp Rating	8	8	8
Energy Consumption (DOE)	2.66 kWh/day	2.91 kWh/day	2.67 kWh/day
Lighting	LED	LED	LED
Refrigerant	R-290	R-290	R-290
Lock Type	T-Handle	T-Handle	T-Handle
Capacity per Column			
12oz. Can	68	68	80
20oz. PET Bottle**	30	30	36



- · ADA compliant, UL certified, ENERGY STAR qualified, meets or exceeds DOE & EPA requirements and is suitable for indoor or outdoor locations.
- · Energy management features included on every model make the V21 one of the most energy efficient machines available: LED lighting, real time clock, lighting and refrigeration controls, cyclopentane injected foam insulation (HFC free) and now the option of R290 (HC) Powered Refrigeration Systems.
- · Full function MDB controller with DEX/UCS, recycler and wireless telemetry compatibility standard on all models.
- The V21 stack allows for maximum flexibility during product loading and most products can be loaded caps to back, butt-to-butt, or in combination.
- The V21 utilizes 24 volt, DC motors that are installed with only two screws for easy servicing. No micro-switches or timing cams!
- 3DVIS door is designed to be easily replaced/refurbished without sacrificing security. It is available as an after-market part and shares common parts with the standard Coca-Cola Chameleon door.







SandenVendo America, Inc. offers a complete line of parts, accessories, supplies and add-on security devices - call for more information.

COCA-COLA, and the COCA-COLA logo design are registered trademarks of The Coca-Cola Company.



SandenVendo America, Inc.

10710 Sanden Drive, Dallas, TX 75238 P: 214-765-9066 F: 214-340-8029 P: 1-800-344-7216 F: 1-800-541-5684

www.vendoco.com

