

Self-Contained Refrigerated Showcase



RSC4SH

Product Summary

Models	RSC3SH and RSC4SH	
Environmental Conditions	NSF/ANSI 7 Type II Standard, maximum indoor 80°F & relative humidity 55%	
External Dimensions	Width	RSC3SH: 37.9" RSC4SH: 49.9"
	Depth	36.1"
	Height	75.6"
Structure	Outer / Inner Box	Powder coated steel / zinc coated steel
	Insulation	Rigid insulating foam
Color (Interior/Exterior)	Standard: Black/Black Optional: Black/Stainless	
Shelves	4 shelves, adjustable powder coated steel frame, glass inserts standard	
Shelf Load Limit	100 lbs. per shelf (glass inserts); 150 lbs. per shelf (with optional steel inserts)	
Electrical	115 VAC / 60 Hz / 20 Amp, 5-20 Plug	
Fan Motors	ECM high efficiency	
Lighting	LED	
Refrigerant	R290	
Evaporator	Fin tube type	
Compressors	2x 2-3/4 HP Reciprocating	
Controller	Digital programmable controller	
Casters	Four 4" Casters	
Drainpipe	1/2" NPT Female Connector	
Thermometer	NSF-approved thermometer	
Internal Volume	RSC3SH: 17.3 ft ³ ; RSC4SH 22.8 ft ³	
Weight	RSC3SH: 480 lbs.; RSC4SH: 550 lbs.	
Noise	Less than 65 dB at 4 ft.	
Agency Approvals	ETL File #4007858 Conforms to ANSI/UL 471, NSF Conforms to ANSI Std 7 Type II	
Option	Manual Night Curtain	
Accessories	Evapoway Condensate Kit Condensate Pump Steel Shelf Inserts	