



Preserve Your Profits

Our patented, revolutionary refrigeration system utilizes N-TeFe (Non-Thermal Electric Field Energy) Technology. The KuraBan creates an ideal environment for preserving all types of fresh foods, without the need for potentially harmful chemicals, radiation, or added labor inhibiting the oxidation process. The KurBan extends preservation, boosts amino acids, boosts sugar levels, and has an anti-bacterial effect.

It operates in a temperature range between conventional coolers and freezers. The system is available in compact reach-in coolers, walk-in vaults, as well as, industrial warehouses.

Model			KB25HCXXX
	Exterior		Front /Side: Stainless Plate, Top Plate/Back Side: Stainless Plate
Material			Machine room: Stainless Steel Plate, Clear Coating
	Interior		Stainless Steel Plate
	Door		Exterior: Stainless Steel Plate, Clear Coating / Inside: Resin Gasket: Magnet Type
	Insulation		Rigid Foamed Polyurethane (HFC Free)
Cooling Performance Ambient Temp 30°C)	e (No load,		− 21°F ~ 39.2°F
Cooling System	Cooling Capacity		3415 BTUH
	Cooling Control Method		Capillary Tube
	Condenser Coil		Fin Tube Forced Air Cooling Type
	Evaporator Coil		Fin Tube Cool Air Forced Circulation Formula
	Refrigerant		R-290 / Charge Size: 130g
	Temp. Control		Microcomputer Control - Digital Temperature Display Model: Eliwell EWPlus 971
	Defrost Method		Microcomputer Controlled Hot Gas
	Evaporator Fan Motor		115V EC Fan Motor
	Condenser Fan Motor		115V EC Fan Motor
	Condensation Management		Collection and Evaporation with Wicking Material and Forced Air
of Doors			2-Door
f of Shelves			6
Capacity			25.37 ft ³
External Dimensions	Height		77.44"
	Width		48.12"
	Depth		34.45"
Inner Dimensions _	Height		57.1"
	Width		42.78"
	Depth		27.2"
Voltage/Frequency			115v 60Hz
Applicable Outlet Type			NEMA 5-15
Ship Weight			650 lb
Comply with these Standards UL 471 Commercial F UL 923 SB1 (Interlock FCC Part B Class A		ANSI/NSF 7 Commercia	al Refrigerators and Freezers
		UL 471 Commercial Re	frigerators and Freezers CSA C22.2
		UL 923 SB1 (Interlocks)	vendo
		FCC Part B Class A	SandanVanda Amarica
		ASHRAE 72 Energy Cor	nsumption per D.O.E. SandenVendo America, www.vendoco.com +1 800 344 7216