



## Mini Hot Food Displays Impulse Series



HFDM


### Concise and Compact

The compact Mini Hot Food Display provides 3 selling surfaces with over 4 cubic feet of product space, with 4 heating zones that can be individually adjusted to suit the various products held. With lift up front doors, the Mini is perfect for self serve applications.

Model		HFD
Approx. Internal Volume		4.1 ft <sup>3</sup> (116 liters)
Overall Unit	Height	27.6 inches (700 mm)
	Width	24.9 inches (632 mm)
	Depth	19.7 inches (500 mm)
Weight		122 lbs. (55 kg)
Temp. Controlled Hot Plates		(4) 141W
Lamps (Heating & Illumination)		(3) 40W Xenon
Controller (Adjustable Temp.)		4 temperature controls, 100°F-255°F
Timers		12 Timers, programmable for 30min-4 hr (in 30 min increments)
Dual Circulation Fans		Standard
Doors		(3) Polycarbonate
Power		115VAC 60Hz
Amp Rating		6.0 Amps
Accessories	Standard	(4) Removable Wire Racks
	Optional	4 inch Leg Kit

NOTE: The manufacturer reserves the right to make product improvements and change specifications without notice.

\*Models not released for sale pending final development.







# Hot Food Combo Serve Display Impulse Series



HFDC

## Enhanced Performance


The new Hot Food Display and Combo Serve models provide single-wide stainless steel shelves for more storage. No center shelf post, allows for easy clean up. New powerful heaters allow a faster heat-up (185 watts vs. 141 watts), with six heating zones that can be individually adjusted to the various products. The Combo Serve HFDC's swing open front doors and sliding back doors make it perfect for self-serve and employee fill from the back. The HFDC model maintains the same side and front door appearance and size, so that these units will look good side-by-side with existing units. Warm LED lights make the food stand out for increased sales.

Model		HFDC
Approx. Internal Volume		6 ft <sup>3</sup> (170 liters)
Overall Unit	Height	27.6 inches (700 mm)
	Width	35.3 inches (896 mm)
	Depth	19.7 inches (500 mm)
Weight		160 lbs (73 kg)
Approximate Rack/Shelf area in <sup>2</sup> (One shelf per area)		Upper 1 x 380
		Middle 1 x 380
		Bottom 1 x 510
Temp. Controlled Hot Plates		6 zones, 185 W each
Lamps (Illumination)		(3) LED
Controller (Adjustable Temp.)		6 temperature controls, 100°F-270°F
Timers		12 Timers, programmable for 30min-4 hr (in 30 min increments)
Dual Circulation Fans		Standard
Glass		ANSI Standard Z97.1 Tempered
Doors		2 sliding rear, 2 front swing open/self-closing
Power		115VAC 60Hz
Amp Rating		10.0 Amps
Included Accessories		Stainless Steel Racks
Optional Accessories		4 inch Leg Kit
		POP Holders Kit

NOTE: The manufacturer reserves the right to make product improvements and change specifications without notice.



SandenVendo America, Inc  
[www.vendoco.com](http://www.vendoco.com)  
+1 800 344 7216







# High Capacity Hot Food Displays

## Impulse Series



## Serving Looks



HFDH



HFDHC


Not only are the HFDHC and HFDH lines capable of holding high volume, they are also fully customizable to suit your needs. Two adjustable shelves can be arranged to fit full, half, or bun size pans. Fit three wide or two full size pans lengthwise across all selling surfaces. Six heating zones can be individually adjusted to each product for optimal heating and freshness.

The HFDHC features swing open front and sliding back doors, making the case perfect for rear or front load self serve applications. The HFDHC Combo-Serve can be purchased with the controller mounted in the front or rear. This display is designed for holding wrapped or boxed food.

The HFDH has two sliding rear doors only for crew serve and fill, designed for holding unwrapped or wrapped food.

Model	HFDH	HFDHC
Overall Unit	Height	35.1 inches (891.54 mm)
	Width	42.7 inches (1084.58 mm)
	Depth	29.8 inches at base (756.92 mm)
Approx. Internal Volume		14 ft <sup>3</sup>
Weight		276 lbs. (125 kg)
Temp. Controlled Hot Plates		(4) 200W (2) 300W
Lamps (Heating & Illumination)		(6) 40W Xenon
Controller (Adjustable Temp.)	Six temperature controls, 100°F-270°F	
	Rear Mount	Front or Rear Mount
Timers		12 Timers, programmable for 30 min-4 hr increments
Amp Rating		14.7 Amps
Standard Accessories	None	(6) Removable Wire Racks
	None	Removable Lexan Spaced Shelf Guards
Optional Accessories		4" Leg Kit

NOTE: The manufacturer reserves the right to make product improvements and change specifications without notice.





## Ambient Displays Food Service Line




The Ambient Food Display Case features LED lights, three white shelves and over 6 cubic feet of product space. These well-lit displays have 360-degree product visibility, and built-in PoP rails for pricing and product identification. Swing open front doors and sliding back doors are perfect for full and/or self-serving. NSF Certified — quality and safety guaranteed.



Model		AFDC
Model Number		AFDC36001
Approx Internal Volume		6 ft <sup>3</sup> (170 liters)
Dimensions	Height	27.6" (700mm)
	Width	35.3" (896mm)
	Depth	19.7" (500mm)
Approx Weight		130 lbs (59 kg)
Shipping Weight		150 lbs (68 kg)
Lamps		3 LED
Doors		2 sliding rear, 2 front swing open/self-closing
Glass		ANSI Standard Z97.1 Tempered
Power (Case Input)		24VDC (110v adapter included)
Amp Rating		1 amp
Optional Accessories		Double sided sign holder, Bag & tong holders, 4" leg kit
Sanitation Approval		NSF/ANSI 2

NOTE: The manufacturer reserves the right to make product improvements and change specifications without notice.

\* Models not released for sale pending final development.







# Hot Food Display Media Topper

## Impulse Series



Hot Food Display  
Media Topper



Provide your customers with an exceptional experience with the Hot Food Display Media Topper! Display still images or video content and audio directly to the customer at the point of sale.


The HFD Media Topper features a 24" Full-HD Ultra HDMI Digital Media player for-MKV/RM- HDD USD Drives and SD Cards with remote control.

An additional area of the front face of upper housing decal bordering the video screen is available for application of a custom-designed decal (not included unless special arrangements are made subject to volume purchases).

Experience an upgraded ad program with the HFD Media Topper by promoting new products and offers, display menus, and sell advertisement space.

Model	HFD Media Topper	
Overall Size	Width	35.8 in
	Height	45.7 in
	Depth	3.0 in
Upper Housing Size	Width	34.8 in
	Height	19.0 in
	Depth	3.0 in
Monitor	24" Television with HDMI input and remote control	
Media Player	1080p Full-HD Ultra HDMI Digital Media Player for -MKV/RM- HDD USD Drives and SD Cards with remote control	
Input Power	110V Power Strip	
Weight	25 lbs.approximately	

NOTE: The manufacturer reserves the right to make product improvements and change specifications without notice.



Hot Food Display Media Topper



**SandenVendo America, Inc**  
[www.vendoco.com](http://www.vendoco.com)  
+1 800 344 7216



# Open Hot Food Display Cases Impulse Series



HFOD24 Open Hot  
Food Display Case



HFOD36 Open Hot  
Food Display Case

## Open Options

With rounded side glass for 360° visibility of your products, the Open Display line has the same stylish appearance as the full line of SandenVendo Hot Food Displays.


The HFOD models have the same height and side glass profile as our HFD, HFDC and HFDM. This allows for multiple models to be lined up side-by-side to serve both wrapped and unwrapped products.




Model	HFOD24	HFOD30	HFOD36	HFOD42	HFOD48	HFOD54	HFOD60	
Overall Unit	Width	27.5 in (698.5 mm)	33.5 in (850.9 mm)	39.5 in (1003.3 mm)	45.5 in (1155.7 mm)	51.5 in (1308.1 mm)	57.5 in (1460.5 mm)	63.5 in (1612.9 mm)
	Depth	31.5.inches (800.1 mm)						
	Height	27.8 inches (706.12 mm)						
Hot Plate	Width	24 in (609.6 mm)	30 in (762 mm)	36 in (914.4 mm)	42 in (1066.8 mm)	48 in (1219.2 mm)	54 in (1371.6 mm)	60 in (1524 mm)
	Depth	24 inches (609.6 mm)						
Voltage				208 - 240				
Watts	1781	2242	2679	3121	3579	4018	4453	
Amps	8.6	10.8	12.9	15.0	17.2	19.3	21.4	
Plug NEMA	L14-20				L14-30			
# of 40 Watt Xenon Lamp(s)	2	4	4	4	6	6	6	
# of Divider Rods (Per Shelf)	4	5	6	7	8	9	10	
Weight	159 lbs. (72.12 kg)	170 lbs. (77.11 kg)	181 lbs. (82.10 kg)	192 lbs. (87.09 kg)	203 lbs. (92.08 kg)	214 lbs. (97.07 kg)	225 lbs. (102.06 kg)	

NOTE: The manufacturer reserves the right to make product improvements and change specifications without notice.



### Adjustable Shelves (patent pending)




Flat Position



7° Tilted Position



HFOD24



HFOD36



SandenVendo America, Inc  
www.vendoco.com  
+1 800 344 7216

### Options

- Polycarbonate Door Kits\*
  - Designer Color Kits for side decals, bottom front base and front of shelves\*
- Standard Color: stainless steel

Optional Colors: black, red, silver, white or green

- Sneeze Guard 5" polycarbonate\*

\*Options under development



## Hot Food Open Topper Impulse Series



### Top of the Line



\*Roller grill not included.

The Hot Food Open Topper is the first equipment solution that combines the power of the roller grill and a Grab and Go Display. When combining these two powerful impulse purchase equipment solutions, sales will increase by utilizing previously unused space.

With two sizes available for the Hot Food Open Topper, you'll be able to fit most common roller grills sold in the U.S.

The Topper features 360 degree product visibility, stylish design and Xenon lamps.


It's a great way to introduce new products and combine product offerings and promotions!

Model	HFOT24001	HFOT24002	HFOT36001	HFOT36002
Overall Unit	Height	29.2 inches (741.68 mm)	33.2 inches (817.88 mm)	29.2 inches (741.68 mm)
	Width	27.5 inches (698.5 mm)	39.5 inches (1003.3 mm)	
	Depth	31.2 inches (792.48 mm)		
Internal Unit	Width	24 inches (609.6 mm)	36 inches (914.4 mm)	
	Depth	24 inches (609.6 mm)		
Approx. Product Weight		141 lbs. (63.96 kg)	166 lbs. (75.30 kg)	
Operation Voltage		120v		
Watts*		759	1118	
Amp Rating*		6.3 Amps	9.3 Amps	
Plug NEMA		L5-15		
Glass		ANSI Standard Z97.1 Tempered		
Safety Approvals		UL 197, CSA C2202 (Pending)		
Sanitation Approval		NSF/ANSI Standard 4 (Pending)		
Accessory		Bag & Tong Holder		



\* Watts/amps are preliminary pending UL evaluation.

NOTE: The manufacturer reserves the right to make product improvements and change specifications without notice.


HFOT24001





HFOT36001



HFOT24002



HFOT36002



SandenVendo America, Inc  
www.vendoco.com  
+1 800 344 7216





# Refrigerated Display Cases

## Impulse Series



RSC6 Refrigerated Display Case



RSC4 Refrigerated Display Case



RSC3 Refrigerated Display Case

## Joinable Design

Quiet and energy efficient, the RSC models perform three timed defrosts per day and use MODBUS communication protocol to allow for online monitoring and set-point adjustments to be made from a central location using an EMS system.

Extended depth and a low deck allow for increased storage and product capacity, the modular design allows for any RSC model to be joined with each other to create multiple width configurations.


The RSC3 and RSC4 come with 7 adjustable glass shelves and the RSC6 come with 14 (7 per side). Top 5/10 shelves can be tilted, with metal shelves and peg rack options available.

Black/Black color standard. White/White color optional.

Model		RSC3	RSC4	RSC6
Product Temperature		Maintain product temperature at or below 41°F		
Environmental Conditions		NSF/ANSI 7 Type II Standard maximum indoor 80°F, Relative Humidity 54%		
External Dimensions	Width	37.9 inches	49.9 inches	73.5 inches
	*Width - Joined Cases	When joining multiple RSC models, subtract (1.35"×2) for the two side panels not used between each joined display.		
	Depth	36.1 inches		
	Height	75.6 inches		
Structure	Outer/Inner Box	Powder coated steel/zinc coated steel		
	Insulation	Rigid Insulating Foam		
Shelves		7 shelves	7 shelves	14 shelves (7 per side)
		Adjustable powder coated steel frame, glass inserts standard (Optional: metal inserts)		
Electrical Parts 115/60/1 (3 Amp)	Fan Motor	ECM high efficiency		
	Lighting	LED (24 VDC)		
	Solenoid Valve	Hermetic direct acting solenoid valve for refrigeration (24V DC)		
Pipe Size of Connection Point	Liquid Line	3/8 inch OD		
	Suction Line	5/8 inch OD		
Refrigerant		R404A, R448A, R407A		
Evaporator		Fin Tube Type		
Expansion Valve		External Equalized Automatic Thermal Expansion Valve		
Controller		Digital programmable controller with Modbus communication protocol		
Casters		(4) 2 inch Casters		
Drain Pipe Dimension		1.5 inch NPT Male Connector		
Thermometer		NSF Certified		
Internal Volume		20.73 ft <sup>3</sup>	41.46 ft <sup>3</sup>	41.46 ft <sup>3</sup>
Weight		368 lbs	405 lbs	598 lbs
Noise		Less than 65 dB at 4 ft		
Agency Approvals		ETL File # 4007858 ANSI/UL 471, NSF/ANSI Std 7 Type II, CAN/CSA C22.2 No. 120, Ed: 3		

NOTE: The manufacturer reserves the right to make product improvements and change specifications without notice.

\*Models not released for sale pending final development.







## Refrigerated Display Cases Impulse Series



RSC6 Refrigerated Display Case

Showcase your wine selection with the sleek stainless steel RSC Line!

Quiet and energy reducing, the RSC models perform two timed defrosts per day and use MODBUS communication protocol to allow for online monitoring and set-point adjustments to be made from a central location using an EMS system. With an extended depth and low deck to allow for increased storage and product capacity, the joinable design allows for any RSC model to be placed with each other to create multiple width configurations.

The RSC3 and 4 come with three adjustable metal shelves plus the bottom panels for a total of four rows of merchandise storage/display. The RSC6 comes with six adjustable metal shelves plus the bottom panels for a total of four rows of merchandise storage/display.



Model		RSC3	RSC4	RSC6
Product Temperature		Maintain product temperature at or below 41°F		
Environmental Conditions		NSF/ANSI 7 Type II Standard maximum indoor 80°F, Relative Humidity 54%		
External Dimensions	Width	37.9 inches	49.9 inches	73.5 inches
	*Width - Joined Cases	When joining multiple RSC models, subtract (1.35"×2) for the two side panels not used between each joined display.		
	Depth	36.1 inches		
	Height	75.6 inches		
Structure	Outer/Inner Box	Stainless steel (including outer valance)/zinc coated (black powder coated) steel		
	Insulation	Rigid Insulating Foam		
Shelves		3 shelves (plus bottom panel)	6 shelves (plus bottom panel)	
		Adjustable powder coated metal frame.		
Electrical Parts 115/60/1 (3 Amp)	Fan Motor	ECM high efficiency		
	Lighting	LED		
	Solenoid Valve	Hermetic direct acting solenoid valve for refrigeration (24V DC)		
Pipe Size of Connection Point	Liquid Line	3/8 inch OD		
	Suction Line	5/8 inch OD		
Refrigerant		R404A, R448A, R407A		
Evaporator		Fin Tube Type		
Expansion Valve		External Equalized Automatic Thermal Expansion Valve		
Controller		Digital programmable controller with Modbus communication protocol		
Casters		(4) 2 inch Casters		
Drain Pipe Dimension		1.5 inch NPT Male Connector		
Thermometer		Product Simulation Thermometor		
Internal Volume		20.73 ft³	27.75 ft³	41.46 ft³
Weight		368 llbs	405 lbs	598 lbs
Noise		Less than 65 dB at 4 ft		
Agency Approvals		ETL File # 4007858 ANSI/UL 471, NSF/ANSI Std 7 Type II, CAN/CSA C22.2 No. 120, Ed: 3		

NOTE: The manufacturer reserves the right to make product improvements and change specifications without notice.





# Open Air Island Merchandiser

## Impulse Series



## Open Air Design




The NIC Open Air Island Merchandiser is specially designed and proven to perform in C-Store and Retail environments. Its open, no door design maximizes product visibility and increases valuable impulse sales. The open air design eliminates worries over customers leaving doors open which can adversely affect product temperature. Without doors, the NIC Open Air Island Merchandiser can maintain a steady product temperature which improves product quality.

6 ft Frozen Food Merchandiser

Model		NIC 183R01	NIC 183S01	NIC 143S01
Product Temperature		Integrated Avg. Temperature -15°F (-26.1°C), (Max product temperature 12°F (-11.1°C))		
Environmental Conditions		Maximum indoor 80°F (26.7°C) and relative humidity 55%		
Ice Cream Set point		-11°F (-23.9°C)		-8°F (-22.2°C)
Ice Cream Setpoint Range		-13°F (-25°C) to -8°F (-22.2°C)		
Freezer Setpoint		0°F (-17.8°C)		
Freezer Setpoint Range		-3°F (19.4°C) to 10°F (-12.2°C)		
External Dimensions	Width	72.4 inches (1838.96 mm)		55.9 inches (1419.86 mm)
	Depth	35.8 inches (909.32 mm)		
	Height	40.0 inches (1016 mm)		
Outer/Inner Box		Powder coated steel/zinc coated steel		
Insulation		Rigid insulating foam		
Color		White		
Baskets		32 baskets		24 baskets
Power		220 VAC, 12 amp, 60 HZ, 1 phase		
Outdoor Condensing Unit		230 VAC, 12 amp, 60 HZ, 3 phase	N/A	
Power Cord/Plug		Length 8 ft 3 wire 16G / Plug Type NEMA L6-20P		
Fan Motors		ECM high efficiency		
Compressor		Outdoor Reciprocating	Horizontal Scroll	
Liquid Line		3/8 inch OD	N/A	
Suction Line		1/2 inch OD	N/A	
Refrigerant		R404A		R449A
Evaporator		Fin tube type, forced convection		
Expansion Valve		External equalized automatic thermal expansion valve		
Controller		Digital programmable controller with Modbus communication protocol		
Casters		(5) 2-inch diameter casters		(4) 2-inch diameter casters
Internal Volume		16.4 ft <sup>3</sup>		12.7 ft <sup>3</sup>
Weight		Approx. 450 lbs. (204.12 kg)	Approx. 520 lbs. (235.87 kg)	Approx. 385 lbs. (174.63 kg)
Agency Approvals		ANSI/UL 471, CSA C22.2, NSF/ANSI 7		
		ETL File #4007858		



4.5 ft Frozen Food Merchandiser



**SandenVendo America, Inc**  
www.vendoco.com  
+1 800 344 7216



Copyright © 2016 SVA

NOTE: The manufacturer reserves the right to make product improvements and change specifications without notice.